

metric system

Bellow ID mm	Bellows OD mm	Number of ply n	Maximum Convolution W	HB neck Execution mm	SAG neck Execution mm	AB neck Execution mm	Operating Pressure bar	Effective Area cm2
10.1	14.5	1	218	10.2	13.2	13.0	34	1.22
10.2	14.5	2	144	10.4	13.2	13.0	94	1.25
10.5	14.5	3	114	10.6	13.2	13.0	125	1.29
13.6	20.0	1	174	13.7	18.2	18.5	15	2.27
13.8	20.0	2	144	13.9	18.2	18.5	40	2.32
14.0	20.0	3	114	14.1	18.2	18.5	82	2.37
15.1	22.0	1	228	15.2	18.5	20.0	20	2.77
15.3	22.0	2	109	15.4	18.5	20.0	52	2.83
15.5	22.0	3	114	15.6	18.5	20.0	97	2.89
18.1	27.0	1	181	18.2	24.2	25.0	10	4.09
18.3	27.0	2	86	18.4	24.2	25.0	27	4.16
18.6	27.0	3	85	18.6	24.2	25.0	60	4.25
19.5	29.0	1	168	19.7	26.7	26.5	10	4.72
19.8	29.0	2	81	19.9	26.7	26.5	25	4.82
20.0	29.0	3	83	20.1	26.7	26.5	45	4.90
21.6	31.5	1	400	21.7	28.5	29.0	8	5.65
21.8	31.5	2	200	21.9	28.5	29.0	20	5.73
22.0	31.5	3	200	22.1	28.5	29.0	40	5.82
25.1	36.5	1	351	25.2	34.2	34.0	6	7.59
25.3	36.5	2	171	25.4	34.2	34.0	16	7.69
25.3	36.5	3	170	25.6	34.2	34.0	30	7.75
27.6	39.5	1	328	27.7	37.2	37.0	6	8.99
27.9	39.5	2	165	27.9	37.2	37.0	15	9.13
27.9	39.5	3	164	28.1	37.2	37.0	28	9.19
29.1	41.5	1	312	29.2	39.2	39.0	6	9.95
29.3	41.5	2	154	29.4	39.2	39.0	14	10.07
29.5	41.5	3	156	29.6	39.2	39.0	27	10.18
31.5	45.0	1	289	31.7	42.2	42.0	7	11.69
31.7	45.0	2	147	31.9	42.2	42.0	13	11.83
31.9	45.0	3	149	32.1	42.2	42.0	25	11.96
35.0	50.0	1	263	35.2	47.2	47.0	5	14.42
35.2	50.0	2	130	35.4	47.2	47.0	12	14.57
35.4	50.0	3	131	35.6	47.2	47.0	24	14.73
40.0	55.0	1	261	40.2	51.7	51.5	5	17.97
40.2	55.0	2	129	40.4	51.7	51.5	12	18.14
40.5	55.0	3	132	40.6	51.7	51.5	20	18.35
44.0	60.0	1	241	44.2	56.2	56.0	5	21.51
44.2	60.0	2	119	44.4	56.2	56.0	11	21.70
44.4	60.0	3	122	44.7	56.2	56.0	18	21.89
49.0	66.0	1	231	49.2	62.2	62.0	5	26.30
49.2	66.0	2	114	49.4	62.2	62.0	12	26.54
49.4	66.0	3	115	49.6	62.2	62.0	23	26.77
57.4	77.0	1	202	57.7	73.2	72.0	4	35.89
57.7	77.0	2	98	57.9	73.2	72.0	10	36.21
57.9	77.0	3	99	58.1	73.2	72.0	17	36.49
61.9	82.0	1	58	62.2	75.2	76.5	5	41.14
62.1	82.0	2	52	62.4	75.2	76.5	12	41.46
68.4	90.0	1	35	68.7	84.2	84.0	4	49.81
68.7	90.0	2	35	69.0	84.2	84.0	11	50.23
77.8	100.0	1	33	78.2	93.7	93.5	4	62.66
78.5	100.0	2	34	78.5	93.7	93.5	10	63.40
94.7	120.0	1	30	95.2	108.0	114.0	3	91.25
94.0	121.0	2	28	95.5	108.0	115.0	6	91.89
104.7	132.0	1	27	105.2	125.2	125.0	2.5	110.85
105.0	132.0	2	26	105.2	125.2	125.0	7	111.48
Bellow ID mm	Bellows OD mm	Number of ply n	Maximum Convolution W	HB neck Execution mm	SAG neck Execution mm	AB neck Execution mm	Operating Pressure bar	Effective Area cm2

